

Section 8: Division 26—Electrical

	Description	Rev	Normal	Difficult	Very Difficult	Company Experience	Unit
	Plastic Bushing Only						
	1/2-inch		0.10	0.12	0.15		E
	3/4-inch		0.12	0.14	0.17		E
	1-inch		0.13	0.17	0.20		E
	1 1/4-inch		0.17	0.21	0.25		E
	1 1/2-inch		0.20	0.25	0.30		E
	2-inch		0.27	0.33	0.40		E
	2 1/2-inch		0.33	0.42	0.50		E
	3-inch		0.40	0.50	0.60		E
	3 1/2-inch		0.47	0.58	0.70		E
	4-inch		0.53	0.67	0.80		E
	5-inch		0.63	0.80	0.97		E
	6-inch		0.77	0.97	1.17		E
	Rigid Conduit Locknut Only						
	1/2-inch		0.10	0.12	0.15		E
	3/4-inch		0.12	0.14	0.17		E
	1-inch		0.13	0.17	0.20		E
	1 1/4-inch		0.17	0.21	0.25		E
	1 1/2-inch		0.20	0.25	0.30		E
	2-inch		0.27	0.33	0.40		E
	2 1/2-inch		0.33	0.42	0.50		E
	3-inch		0.40	0.50	0.60		E
	3 1/2-inch		0.47	0.58	0.70		E
	4-inch		0.53	0.67	0.80		E
	5-inch		0.63	0.80	0.97		E
	6-inch		0.77	0.97	1.17		E
	Lock Nut & Ground Bushing Sets - Field Cut & Thread Included						
	<i>Notes: Add 25% for stainless steel conduit & fittings</i>						
	<i>- Termination of grounding conductor is not included</i>						
	1/2-inch		0.40	0.50	0.60		E
	3/4-inch		0.45	0.56	0.67		E
	1-inch		0.50	0.62	0.75		E
	1 1/4-inch		0.60	0.75	0.90		E
	1 1/2-inch		0.80	1.00	1.20		E
	2-inch		1.00	1.25	1.50		E
	2 1/2-inch		1.20	1.50	1.80		E
	3-inch		1.40	1.75	2.10		E
	3 1/2-inch		1.60	2.00	2.40		E
	4-inch		1.90	2.35	2.85		E
5-inch		2.20	2.75	3.30		E	
6-inch		2.70	3.40	4.00		E	
	Ground Bushing Only						
	<i>Notes: Add 25% for stainless steel conduit & fittings</i>						
	<i>- Termination of grounding conductor is not included</i>						
	1/2-inch		0.15	0.18	0.23		E
	3/4-inch		0.16	0.20	0.24		E
	1-inch		0.21	0.26	0.32		E
	1 1/4-inch		0.31	0.39	0.47		E
	1 1/2-inch		0.41	0.51	0.62		E
	2-inch		0.51	0.64	0.77		E
	2 1/2-inch		0.61	0.76	0.92		E
	3-inch		0.71	0.89	1.07		E
	3 1/2-inch		0.81	1.01	1.22		E
	4-inch		0.91	1.14	1.37		E
5-inch		1.01	1.26	1.52		E	
6-inch		1.10	1.39	1.67		E	
	Factory Cut Rigid Steel Nipples - Up to 12-inch Length Maximum						
	<i>Note: Add 25% for stainless steel conduit & fittings</i>						
	1/2-inch		0.25	0.31	0.37		E
	3/4-inch		0.30	0.37	0.45		E
	1-inch		0.35	0.43	0.52		E
	1 1/4-inch		0.40	0.50	0.60		E
	1 1/2-inch		0.50	0.62	0.75		E
	2-inch		0.60	0.75	0.90		E
	2 1/2-inch		0.75	0.94	1.12		E
	3-inch		0.90	1.12	1.35		E
	3 1/2-inch		1.10	1.37	1.65		E
	4-inch		1.30	1.62	1.95		E
	5-inch		1.50	1.87	2.25		E
6-inch		1.80	2.25	2.70		E	